

TECHNICAL DATA SHEET

CERAMIC MATT EMULSION
WIPEABLE WATERBORNE ACRYLIC INDOOR PAINT

Product Type

Ceramic matt, waterborne paint with extremely good coverage. Odour-free paint with good scratch resistance and wipeable features. These properties are reached through the use of ceramic microspheres. This paint is both base and top coat for interior walls.

Areas of Application

Specially aimed for a smooth matt finish on walls and ceilings. This product can be applied on substrates made from gypsum plaster, particleboard etc. Suitable for all rooms including high traffic areas.

Special Properties

- Ceramic matt emulsion paint
- Water based
- Environmentally friendly
- Great coverage
- Wipeable
- No splashes
- Gloss level: 2-3% matt
- Suitable for domestic and professional use

Surface Preparation

The substrate which is to be painted should be clean, dry and dust-free for good adhesion. Prepare surface as per our decorating advice. Glossy surfaces should be sanded to matt. Newly plastered walls should be allowed to dry, this may take up to 4 weeks. We recommend applying a base coat of 50% water, 50% white matt emulsion for newly plastered walls as well as for walls which currently are painted a darker shade. We are not recommending to use any vinyl-base undercoats with our Ceramic Matt Ceramic Emulsion.

Application Information

The paint is ready to use (ensure goods are stirred thoroughly before use). Apply with a roller/brush or spray application. After light diluting with water, the product is ready for spraying. When applying tinted paint always try to apply complete areas with paint from the same can. The paint has a soft structure in order to achieve an even surface. In order to get an even result, when the paint is applied by roller, it is important that the roller is moved with soft pressure in the same direction over the surface. The same paint can be used both as base and top-coat. We recommend 2 coats of paint, depending on type and colour of surface which you are painting. Check for full coverage after the coating is completely dry.

Coating Conditions

Apply under controlled conditions, where air, paint and surface temperature should never be below +5°C. At very high humidity the drying time will be longer.

Wipeable Feature

AVKO INTERIOR PAINTS

TECHNICAL DATA SHEET

One of the major benefits to our interior paint is that it is entirely wipeable. This means that, should you need to wipe off any marks or scuffs you can do so. All you need to accomplish this is a soft sponge and warm water. Softly brush the wet sponge over the marks on the painted wall and watch them disappear.

Technical Data Sheet

Covering	Depending on type of surface, 5-9 m ² /litre
Resin	Styrene acrylic reinforced with ceramic microspheres
Solid content	41 % pro volume
Density	1,45 kg/litre
Viscosity	180-190 cP
Thinner/cleaner	Water
Application	Roller, brush or spray
Drying time	Touch dry/Repaintable 1 hour Totally dry 3 hours At 20°C and max 85% humidity
Gloss	2-3% matt. measured at Gardner 60°
Colour	White Base A
Wash ability	15000 laps according ISO 6504-3. Class 1 acc. DIN 13300
Storage time	2 year in unopened can, frostless
Packaging	1 Litre, 2.5 Litres, 5 Litres

Eco – signs



Individual safety

Avoid skin and eye contact and inhalation of dust and spray mist.

Keep out of reach of children. Contains biocidal products: 1,2-benzisothiazol-3(2H0-onem C(M)IT/MIT (3:1). May produce an allergic reaction.

This product contains a maximum of 30g VOC/L. The limit value is 30g VOC/L (cat A/a)

Environmental protection

WWW.AVKOINTERIOR.CO.UK



TECHNICAL DATA SHEET

Do not allow into drains or water courses.

Dispose in accordance with regulations from authorities

