

TECHNICAL DATA SHEET

Madreperla Feature Wall

Product type

WIPEABLE WATERBASED INDOOR PAINT

Madreperla is a pearly soft textured finish paint for interior walls, that creates a unique luxury finish. Madreperla can also be infused with our glitter to add that extra shimmer to your room.

Areas of application

Madreperla has been designed to be a feature wall paint for interior spaces and can be applied on substrates made from gypsum plaster, particleboard etc. Madreperla can be applied with either a brush/roller or spray application.

Special properties

Madreperla is entirely water based which makes it eco-friendly and safe, as well as odourless. This fast drying product creates a pearlescent finish.

Surface preparation

The substrate which is to be painted should be clean, dry and dust-free for good adhesion. Prepare surface as per our decorating advice. Glossy surfaces should be sanded to matt. Newly plastered walls should be allowed to dry, this may take up to 4 weeks. We recommend applying a base coat of 50% water, 50% white matt emulsion for newly plastered walls as well as for walls which currently are painted a darker shade.

Application information

The paint is ready to use (ensure goods are stirred thoroughly before use). Apply using a brush/roller or spray application. When applying tinted paint always try to apply complete areas with paint from the same can. This paint will produce a pearly soft textured effect. We recommend 2-3 coats of paint, depending on type and colour of surface which you are painting. Check for full coverage after the coating is completely dry. Please refer to our video tutorial on our website for full details.

Coating conditions

Apply under controlled conditions, where air, paint and surface temperature should never be below 10°C or above 50°C. At very high humidity the drying time will be longer.

Wipeable Feature

One of the major benefits to our interior paint is that it is entirely wipeable. This means that, should you need to wipe off any marks or scuffs you can do so. All you need to accomplish this is a soft sponge and warm water. Softly brush the wet sponge over the marks on the painted wall and watch them disappear.

TECHNICAL DATA SHEET

Technical Data Sheet

Covering	Depending on type of surface, 5-8 m ² /litre
Density	1.1-1.15 kg/litre
Thinner/cleaner	Ready to use
Application	Brush, roller & spray
Drying time	Touch dry 1 – 2 hours Recoat 4 – 6 hours At 20°C and max 80% humidity
Finish	Pearlescent finish (glitter can be added for a pearlescent glitter finish)
Storage time	18 months, with temperature max of 38°C, in unopened sealed can, indoors and protected against freeze.
Packaging	1 litre, 2.5 Litres, 5 Litres
Cleaning	Wash equipment with water immediately after use



Individual safety

Avoid skin, eye contact and inhalation of dust and spray mist.

Keep out of reach of children.

This product contains < 10g VOC/L.

Environmental protection

Do not allow into drains or water courses.

Dispose in accordance with regulations from authorities