

TECHNICAL DATA SHEET

Sealer Filler Wood Primer
WATERBASED INTERIOR PRIMER

Product type

Sealer Filler Wood Primer is an easy to use, water-based, 1 -2 coat primer for interior use. It can be easily sanded and can be applied by brush or spray. It's especially good for filling porous coatings and adheres well to vertical surfaces. For application on to MDF, plywood and other wood-based products.

Special properties

The sealer filler wood primer is a high-quality product that is designed for use on MDF, wood, or wood-based boards for furniture, interiors, shop fittings and kitchens. A surface that has been primed with our sealer filler wood primer, will provide a great base for a high-quality colour coating.

Surface preparation

The surface must be well-cleaned using a damp cloth in order to be free from grease and oil, it should then be allowed to dry before application. The open edge must be sanded back using 180 grit paper to ensure adhesion to the open edge. The remainder of the surface should be sanded down with 320 grit paper to smooth the substrate before application. The product should be stirred before application. If required, the product can be thinned with water.

Application information

Our wood primer can be applied using a regular brush or a spray gun, and will cover in 1 – 2 coats depending on the surface being primed. Please refer to our video tutorial for full application details.

Coating conditions

Apply under controlled conditions, temperature should be maintained at a minimum of 15°C at all times during application and drying.

TECHNICAL DATA SHEET

Technical Data Sheet

Covering	For brush application: 9.5m ² per litre For spray application: 4m ² per litre
Resin	1k Polymer Dispersion
Solid content	66 % pro volume
Density	1.53 g/cm ³
Thinner/cleaner	Ready to use. The viscosity can be adjusted by adding max 5% water if required.
Application	Brush and spray
Drying time	<u>Brush application:</u> Touch dry after 4 -5 minutes Suitable for recoating after 15 minutes <u>Spray gun application:</u> Touch dry after 9 – 10 minutes Suitable for recoating after 10 minutes At 20°C and max 65% humidity
Gloss	Matt finish
Colour	White
Storage time	12 months in unopened can, frostless
Packaging	1 litre, 2.5 Litres



Individual safety

Avoid skin, eye contact and inhalation of dust and spray mist.

Keep out of reach of children.

Environmental protection

Do not allow into drains or water courses.

Dispose in accordance with regulations from authorities