

TECHNICAL DATA SHEET

Product type

Sharazade (Lux) Feature Wall **WIPEABLE WATERBASED INDOOR PAINT**

Sharazade is a luxury textured finish, achieved through the use of a metallic pigment which gives it a rough reflective effect. Both Sharazade and Sharazade Lux are available in two versions, "light" (the standard Sharazade finish) and "plus" (for a more textured option).

Areas of application

Sharazade has been designed to be a feature wall paint for interior spaces and can be applied on substrates made from gypsum plaster, particleboard etc. We recommend applying Sharazade with a coarse brush.

Special properties

Sharazade is entirely water based which makes it eco-friendly and safe, as well as odourless. This fast drying product creates a unique luxury textured effect which is easy to achieve with Sharazade paint.

Surface preparation

The substrate which is to be painted should be clean, dry and dust-free for good adhesion. Prepare surface as per our decorating advice. Glossy surfaces should be sanded to matt. Newly plastered walls should be allowed to dry, this may take up to 4 weeks. We recommend applying a base coat of 50% water, 50% white matt emulsion for newly plastered walls as well as for walls which currently are painted a darker shade.

Application information

The paint is ready to use (ensure goods are stirred thoroughly before use). Apply using a coarse brush. Sharazade can be applied using a variety of brush strokes to create a unique and personal pattern. When applying tinted paint always try to apply complete areas with paint from the same can. The paint contains a metallic pigment and will leave a rough textured finish. We recommend 2 coats of paint, check for full coverage after the coating is completely dry. Please refer to our video tutorial on our website for full details.

Coating conditions

Apply under controlled conditions, where air, paint and surface temperature should never be below 10°C and above 50°C. At very high humidity the drying time will be longer.

Wipeable Feature

One of the major benefits to our interior paint is that it is entirely wipeable. This means that, should you need to wipe off any marks or scuffs you can do so. All you need to accomplish this is a soft sponge and warm water. Softly brush the wet sponge over the marks on the painted wall and watch them disappear.

AVKO INTERIOR PAINTS

TECHNICAL DATA SHEET

Technical Data Sheet

Covering	Depending on type of surface, 5-8 m ² /litre
Density	1.100 – 1.150 kg/dm ³
Thinner/cleaner	Ready to use
Application	Brush
Drying time	Touch dry 1 – 2 hours Recoat 4 – 6 hours At 20°C and max 80% humidity
Finish	Metallic finish textured feature wall paint
Storage time	18 months, with temperature max of 38°C, in unopened sealed can, indoors and protected against freeze.
Packaging	1 litre, 2.5 Litres, 5 Litres
Cleaning	Wash equipment with water immediately after use



Individual safety

Avoid skin and eye contact and inhalation of dust and spray mist.

Keep out of reach of children.

This product contains < 10g VOC/L.

Environmental protection

Do not allow into drains or water courses.

Dispose in accordance with regulations from authorities